



# **Welding Cables**

Copper Conductor HOFR (Heat Oil Fire Retardant ) & TRS (Tough Rubber Sheathed)

Panasonic Welding Copper conductor cables are best in class adhering to International Standard for Copper conductor as per IS:8130-84 & Elastomeric rubber insulation as per IS 6380-84, Type IE1 (TRS Cable) or Type IE3 (HOFR Cable)



**Welding Cable drum** 



HOFR Cable 35 sq mm & 70 sq mm

## **Copper Conductor HOFR Welding Cable**

	Current carrying capacity (Amps) conforming to IS:9857/90							
Cross Section area (sq mm)	No. of 0.3 mm dia strands	Sheath thickness (mm)	Approx. overall diameter (mm)	Max. Resistance @20 deg C (ohm/km)	100%	85%	60%	30%
50	702	2.2	15.3	0.386	280	305	360	510
70	999	2.4	17.3	0.272	350	385	455	645
95	1332	2.6	20.5	0.206	425	460	550	775

# **Welding Cables**

#### **Copper Conductor TRS Welding Cable**

Copper Conductor TRS						Current carrying capacity (Amps) conforming to IS:9857/90			
Cross Section area (sq mm)	No. of 0.3 mm dia strands	Sheath thickness (mm)	Approx. overall diameter (mm)	Max. Resistance @20 deg C (ohm/km)	100%	85%	60%	30%	
35	497	2.0	13.7	0.554	155	170	200	285	
50	702	2.2	15.3	0.386	200	215	255	360	
70	999	2.4	17.3	0.272	250	270	320	455	
95	1332	2.6	20.5	0.206	300	345	385	550	

Ш	Perm	issible	e Wor	king	Temp	:
---	------	---------	-------	------	------	---

TRS : Max 80 deg C

HOFR: Max 100 deg C

## ■ Application industry :

Automobile, Construction, Ship-building, Railways, Mining,

Power, Oil & Gas and so on ..

#### ☐ Safety Precautions

- Must be spread out before use to avoid overheating.
- Cable should be cut after minimum 10 feet of the holder .
- Cable should never be around the welder in a loop/coil form.
- Cables with damaged insulation must be changed quickly.

#### **Panasonic**

For more information please write to <a href="mailto:psfsin.enquiry@in.panasonic.com">psfsin.enquiry@in.panasonic.com</a>
For service related queries ,write to <a href="mailto:welding.info@in.panasonic.com">welding.info@in.panasonic.com</a>
Panasonic India Pvt Ltd.

(Division Company :Panasonic Smart Factory Solutions India ) Factory:

Village Bid Dadri ,Tehsil and District : Jhajjar-124103,Haryana,India Head Office:

12th Floor, Ambience Tower I, Ambience Island NH-8, Gurgaon, Haryana

www.panasonic.com/in/welding